

## Thread Specification

Construction	Count(Ne)	Ticket No	Tex Size	Length(m)	Avg. Strength (lbs)	Avg. Strength (grams)	Avg. Strength (cN)	Elongation %	Ndl. Sz Min
SSP	60/2	180	T-18	4000	1.46	661	648	12-17	70/10
	60/3	120	T-27	2500	2.15	975	956	13-18	75/10
	52/2	120	T-24	4000	1.76	800	786	13-18	75/10
	50/2	130	T-24	4000	1.87	850	829	13-18	70/10
	45/2	120	T-27	4000	2.10	950	931	13-18	75/10
	44/2	120	T-27	4000	2.02	918	900	13-18	75/10
	40/2	110	T-30	4000	2.48	1122	1100	13-19	75/10
	40/3	75	T-45	3000	3.79	1718	1684	13-22	90/14
	30/2	75	T-40	3000	3.19	1448	1420	13-22	90/15
	30/3	50	T-60	2500	5.15	2332	2286	13-22	110/18
	24/2	70	T-50	3000	3.64	1650	1617	13-22	110/18
	24/3	30	T-75	2000	5.63	2550	2500	13-24	120/20
	22/2	50	T-60	3000	4.61	2090	2050	13-22	110/18
	20/2	50	T-60	3000	4.95	2242	2198	13-24	110/18
	20/3	30	T-90	2000	7.84	3550	3480	13-24	120/20
	20/4	25	T-120	1500	10.25	4645	4554	16-24	130/21
	20/6	15	T-180	1000	16.31	7387	7242	16-24	160/23
	20/9	10	T-270	500	22.17	10043	9846	16-24	200/25
	16/3	28	T-105	2000	8.98	4066	3986	13-24	140/22
	12/3	20	T-150	1500	11.79	5339	5234	13-24	140/22
PPC	50/2	130	T-24	4000	2.31	1050	1072	14-22	70/10
	45/2	120	T-27	4000	2.59	1173	1150	14-22	75/11
	40/2	110	T-30	4000	3.11	1408	1380	14-22	80/12
	20/2	50	T-60	3000	6.75	3060	3000	14-27	100/16
	20/3	30	T-90	2000	10.13	4590	4500	14-24	100/16
	20/4	25	T-120	1500	13.24	5996	5878	14-27	110/18
TXP	150(TPM)	180	T-18	4000	1.50	677	664	18-27	60/8
	150(IN)	180	T-18	4000	1.42	642	629	18-27	60/8
	150(SET)	180	T-18	4000	1.30	590	578	18-27	60/8
PVA	40/2	110	T-30	1500	1.41	640	627	12-21	75/11